



552796

(43) International Publication Date
28 October 2004 (28.10.2004)


PCT

(10) International Publication Number
WO 2004/093507 A1

- (51) International Patent Classification⁷: H05K 3/12 (74) Agent: IKEUCHI SATO & PARTNER PATENT ATTORNEYS; 26th Floor, OAP TOWER, 8-30, Tenmabashi 1-chome, Kita-ku, Osaka-shi, Osaka 5306026 (JP).
- (21) International Application Number: PCT/JP2004/005283
- (22) International Filing Date: 14 April 2004 (14.04.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2003-112055 16 April 2003 (16.04.2003) JP
- (71) Applicant (for all designated States except US): MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 5718501 (JP).
- (72) Inventor; and
- (73) Inventor/Applicant (for US only): NAKAGAWA, Tohru.
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: DISCHARGING SOLUTION, METHOD FOR PRODUCING PATTERNS AND METHOD FOR PRODUCING AN ELECTRONIC DEVICE USING THE DISCHARGING SOLUTION, AND ELECTRONIC DEVICE



(57) Abstract: A discharging solution capable of forming patterns with spreading suppressed on the surface of a base without previously forming a complementary repellent region on the surface of the base, a method for forming the patterns, and the like are provided. More specifically, a discharging solution and the like for forming patterns with spreading suppressed on the surface of a base using, for example, an ink-jet method is provided. The discharging solution for forming patterns on the surface of a base include organic molecules having fluoroalkyl chains as a first pattern formation material, and has a surface tension of 20 dyne/cm or more.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*